We claim:

- Open-celled foam beads having a mean bead diameter of from 1 to 10 mm and a bulk density of from 5 to 200 g/l based on propylene polymers and having a proportion of open cells (in accordance with DIN ISO 4590) of greater than 40%.
- Open-celled foam beads as claimed in claim 1, wherein the
 propylene polymer is a homopolymer or copolymer of propylene with up to 15% by weight of ethylene and/or 1-butene.
 - 3. Open-celled foam beads as claimed in claim 1, which have, in the DSC thermodiagram, at least one high-temperature peak at a higher temperature than the melting peak of the propylene polymer employed.
 - 4. Open-celled foam beads as claimed in claim 1, wherein the mean cell diameter is from 0.01 to 0.5 mm.

20

15

- 5. Open-celled foam beads as claimed in claim 1, which have a content of from 1 to 40% by weight of a cell opener.
- 6. A process for the production of open-celled foam beads as claimed in claim 1 by impregnating propylene polymer beads in suspension with a volatile blowing agent in a pressure container at elevated temperature and subsequently decompressing the mixture, wherein the propylene polymer beads comprise from 1 to 40% by weight of a cell opener.

30

7. A process as claimed in claim 6, wherein the blowing agent is an organic compound having a boiling point of between -5 and 150° C, preferably a C_4- to C_6- hydrocarbon, or an inorganic gas.

35

8. A process as claimed in claim 6, wherein the cell opener is a polar, water-insoluble thermoplastic, preferably a polyamide or polyoxymethylene.

40

- 9. A process as claimed in claim 6, wherein the cell opener is a needle-shaped inorganic solid, preferably cut glass having a length of from 0.25 to 5 mm.
- 5 10. A process as claimed in claim 6, wherein the cell opener is a water-soluble polymer, preferably polyvinylpyrrolidone, polyvinyl acetate or polyethylene oxide.
- 11. An open-celled foam molding produced by post-expansion and sintering of the foam beads as claimed in claim 1.

15

20

25

30

35

40